
EJV 93637 150W 21V 24/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54732
Product Name	EJV 93637 150W 21V 24/CS 1/SKU
Ordering Abbreviation	EJV 93637 150W 21V 24/CS 1/SKU
Application	Projector - 8mm, Printer
Product Remark	- Lumens refers to screen lumens.

Electrical data

Nominal Wattage	150 W
Nominal Voltage	21 V
Type of Current	AC

Light technical data

Luminous Flux	270 lm
Working Distance a (in)	1.486 in
Working Distance a (mm)	38.1 mm
Color Rendering Index	100
Average Rated Life	100 h

Physical attributes



Base	GX5.3
Bulb Shape	MR16
Maximum Overall Length (in)	1.689 in
Maximum Overall Length (mm)	43.3 mm
Length l (in)	1.486 in
Length l (mm)	38.1 mm
Length l max. (in)	1.486 in
Length l max. (mm)	38.1 mm
Diameter d (in)	2.008 in
Diameter d (mm)	51.00 mm
Filament	CC-6
Reflector Coating	WHITE

Additional product data

Operating Position	Any
Total surface inside 1: appearance (cold)	CLEAR
Class	C (gas)

Product datasheet

Lamp Type	MR16
-----------	------



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54732	4050300350097	Folding box (SKU)	1	1.7 in x 1.7 in x 2.2 in	0.1 lb
54732	4052899573246	Shipping box (Case)	24	7.8 in x 6 in x 5.5 in	2.2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

- OSRAM does not accept liability for errors, changes and omissions.