# **OSRAM**

# LEDinspect MAX500

# LED Inspectionlights





Multi-Angle Flex & Twist High flexibility due to multiple positioning possibilities



2in1 LED Inspectionlight & UV lamp in one



#### 500 Lumen

Three light functions - high with up to 500 lm, low with up to 250 lm and torchlight function with up to 70 lm



#### 2-year-OSRAM guarantee\*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers



#### Light is versatile

With three light functions - high with up to 500lm, low with up to 250lm and UV torchlight, the MAX500 offers high flexibility and different application possibilities. The 360° twist and 180° flex base give maximum flexibility to be able to adjust the angle of light exactly where needed. The integrated charge indicator shows the charging status of the rechargeable battery - up to 4.5h operating time at high power or up to 7.5h at low power. In accordance with the IP protection class IP65, this inspection light has protection against the ingress of dust and water and is tested for impact resistance in accordance with IK08. This inspection light contains an integrated hook & magnets for hands-free work and easy attachment and is therefore ideal as a light for manual activities, car repairs and in everyday life. In addition, OSRAM grants a 2-year guarantee on this product\* USB charging cable and mains charger included.

Product datasheet | LEDinspect MAX500 © 2024, OSRAM GmbH. All rights reserved.

#### Technical data

### **Product information**

Order reference	LEDIL402
Application (Category and Product specific)	LED inspection lights

#### **Electrical data**

Nominal wattage	16.50 W
Nominal voltage	3.7 V


#### Photometrical data


Color temperature	6000 К
Luminous flux	500 lm
Light color LED	White

## LED module information

Number of LEDs per module	2
---------------------------	---

## **Dimensions & weight**





Product weight	350.00 g
Length	253.0 mm
Width	59.0 mm
Height	44.0 mm

## Colors & materials

Base color	Black / Orange
Dase cotor	Diack / Orange

#### Lifespan

Guarantee

2 years

## Additional product data

Type of Battery	Rechargeable	
Number of included batteries	1	
Scope of battery	Yes	
Battery	High-quality lithium-ion battery	

#### Capabilities

Technology	LED

## Certificates & standards

Standards	CE/EMC/MSDS/ROHS	
IK Class	IK08	

### **Country specific categorizations**

LEDIL402

#### **Environmental information**

# Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of Declaration 07-09-2023		
Primary Article Identifier	4052899623835	
Declaration No. in SCIP database	In work	



Detail

Detail



Detail





Detail

Detail

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899623835	INSPECTION LAMP	Folding carton box 1	90 mm x 50 mm x 262 mm	1.18 dm³	770.00 g
4052899623958	INSPECTION LAMP	Shipping carton box 6	200 mm x 170 mm x 290 mm	9.86 dm³	7420.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Download Data

	File
7	User instruction LEDinspect MAX 500 LEDIL402
D	Movie application LEDinspect Inspection Lights Trailer

#### Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.

\*for precise conditions please refer to:

www.osram.com/am-guarantee

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

