OSRAM LEDguardian TRUCK FLARE Signal TA19

LEDguardian warning- and safety lights





Street legal in Germany Carrying along in the vehicle and positioning of a warning light in the event of a brokendown vehicle is mandatory in Germany for all vehicles $\geq 3.5t$ in accordance with §53a TA19 **StVZO**



2 in 1 LED Warning Light & LED TorchlightBright yellow flashing light & Bright white torchlight



4x AA batteries included Thanks to the included batteries, the warning light is ready for use immediately after purchase



2-year-OSRAM guarantee*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers



Light is safety-See and be seen with OSRAM

Be prepared - with OSRAM LEDguardian warning and safety lights.The OSRAM LEDguardian TRUCK FLARE Signal TA19 is a LED warning light which must be carried along in the vehicle and used in the event of a break-down in Germany. This applies to all vehicles with a total weight of \geq 3.5t according to §53a StVZO. In addition, the TRUCK FLARE from OSRAM also meets the requirements specified in the technical requirements of the StVZO (TA 19). These state that the warning light must fulfill the following characteristics: An orange flashing light, an uninterrupted operating time of at least 15h, a flashing frequency of 1.5 Hz \pm 0.5 Hz \pm 90 \pm pulses per minute and a dynamic pressure 21 kg/m² \doteq wind force 9. Only those lights that meet these requirements are officially approved for use in road traffic. The warning light must be in operation next to the warning triangle to indicate the danger zone in the event of a breakdown or accident. For vehicles \leq 3.5t the use is not mandatory, but for the safety of all road users of course possible and recommended. The flashing orange warning light function of the OSRAM LEDguardian TRUCK FLARE Signal TA19 is visible from a great distance and can provide crucial information about a dangerous situation on the road in an emergency. In addition to the warning triangle, it alerts other road users about a potentially dangerous situation on the road by actively flashing, compared to the simple reflection such as that of a warning triangle. With 6 long-life high-power LEDs with up to 6000K, you can draw attention to yourself by day and night, and preventively alert and warn other road users of a dangerous situation, such as a broken-down vehicle on the road. In addition, the TRUCK FLARE can also serve as a torchlight. As an additional function, a bright white torchlight is integrated and enables additional applications such as a work or inspection light. The compact design allows you to store the warning light within easy reach in the vehicle and, if required, it can be set up quickly and easily directly next to the warning triangle thanks to the foldout, robust and non-slip feet. Another advantage is that the batteries included in the scope of delivery mean that the OSRAM LEDguardian TRUCK FLARE Signal TA19 is immediately ready for operation. The LEDguardian TRUCK FLARE Signal TA19 has been tested and validated in our DIN EN ISO/IEC 17025 certified environmental simulation laboratory for extreme external influences in terms of water, dust, heat, cold and impacts from falls. With an IP54 protection class, the OSRAM LEDguardian TRUCK FLARE Signal TA19 is resistant to the ingress of water and dust. OSRAM provides a 2-year guarantee* on this product.

Technical data

Product information

Order reference	LEDSL103	
Application (Category and Product specific)	Warning and safety lights	


Electrical data

Nominal wattage	1.50/3.0 W	
Nominal voltage	6.0 V	

Photometrical data

Color temperature	2000/6000 К	
Light color LED	Orange / White	

Dimensions & weight



Product weight	600.00 g
Length	90.0 mm
Width	43.0 mm
Height	236.0 mm

Lifespan

Guarantee	2 years

Additional product data

Type of Battery	Alkaline
Scope of battery	Yes
Battery	4X LR6

Capabilities

Technology	LED	
Certificates & standards		
Standards	CE	
Type of protection	IP54	
Country specific categorizations		
Order reference	LEDSL103	

Environmental information

Date of Declaration	12-10-2022
Primary Article Identifier	4062172185967 4062172185943 4062172185929
Declaration No. in SCIP database	In work

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172185967	LEDguardian TA19	Folding carton box 1	100 mm x 50 mm x 255 mm	1.28 dm³	653.00 g
4062172185974	LEDguardian TA19	Shipping carton box 10	255 mm x 210 mm x 290 mm	15.53 dm³	6880.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
7	User instruction LEDguardian TRUCK FLARE Signal TA19
7	Brochures OSRAM LEDguardian Truckflare TA19 Flyer (EN)
D	Movie application Product Video OSRAM LEDguardian TRUCK FLARE Signal TA19 (EN)
D	Movie application Product Video OSRAM LEDguardian TRUCK FLARE Signal TA19 (EN)
D	Movie application LEDguardian ROAD FLARE Signal TA19 Social Media Reel (EN)

D	Movie application LEDguardian ROAD FLARE Signal TA19 Social Media Reel Camper (EN)
D	Video OSRAM LEDguardian TRUCK FLARE Signal TA19 - Camper
	360 Degree Image OSRAM LEDguardian Truckflare TA19

Legal advice

*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice:

For more detailed application information and graphics please see product datasheet and user manual.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

