

XBO 6000 W/HTP XL OFR

XBO for cinema projection | Xenon short-arc lamps 450...10,000 W



Areas of application

- Classic 35 mm film projection
- Digital film and video projection
- Architectural and effect light ("Light Finger")
- Sunlight simulation

Product family benefits

- Short arc with very high luminance for brighter screen illumination
- Constant color temperature of 6,000 K throughout the entire lamp lifetime
- Easy to maintain
- High arc stability
- Instant light on screen thanks to hot restart function
- Wide dimming range

Product family features

- Color temperature: approx. 6,000 K (Daylight)
- Wattage: 450...10,000 W
- Very good color rendering index: R_a >








Product datasheet

Technical data

Electrical data

Nominal current	160 A
Current control range	110165 A
Nominal wattage	6000.00 W
Nominal voltage	37.0 V

Dimensions & weight



Diameter	78.0 mm
Length	430.0 mm
Length with base excl. base pins/connection	382.00 mm
Light center length (LCL)	165.0 mm ¹⁾
Cable/wire length, input side	
Electrode gap cold	9.0 mm
Product weight	933.00 g

 $^{^{1)}}$ Distance from end of base to tip of electrode (cold)

Temperatures & operating conditions

Max. permitted ambient temp. pinch point	230 °C

Lifespan

Additional product data

Base anode (standard designation)	SFa27-14
Base cathode (standard designation)	SFc27-14

Capabilities

Product datasheet

Cooling	Forced ¹⁾
Burning position	p15 ²⁾

¹⁾ Vertical and horizontal

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of Declaration	19-01-2022	
Primary Article Identifier	4008321412911	
Declaration No. in SCIP database	In work	

 $^{^{2)}}$ For vertical burning position: anode (+) on top

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321412911	XBO 6000 W/HTP XL OFR	Shipping carton box	590 mm x 229 mm x 234 mm	31.62 dm ³	2019.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.